


BLG111 Auto Sensing Barcode Laser Scanner

light source	650mm laser		
Error rate	<1 / 200 000		
Security	Class 1 Laser/CE		
Interface	RS232, PS2 KB, USB		
Scanning	Auto sensing and Hand-held		
Brief Specify	Scanner with sensor can be triggerless(autoscan) working or hand-held(trigger) working . User can press the trigger about 10 seconds to switch it to Hand-held tyoe or AutoSensing type. Further, The stand can be curved , more flexable stand for operation..		
Bar code type	UPC-A, UPC-E, Industrial 2of 5, Interieaved 2 of 5, EAN 8.EAN 13, Code 128, EAN 128, Code 39, Code93, Codabar 125, etc.		
Transmission rate	RS232 , Baudrate:2400-38400		
Resolution	(pcs0.9) 0.10mm(4mil)		
Read width	60mm at 30mm (from object)	98mm at100mm (from objects)	
Reading speed	120 scans / sec		
Reading distance	About 25-700mm		
Elevation reading	60 degrees	Read the angle : 45 degrees	
Operating temperature	-20- 45 degrees	humidity - : 20- 45 degrees	
Storage humidity	5%- 85%		
Power Supply	DC +5V/ 30mA		
Drop test	100/1.5m		
By the light intensity	4000 lux max daylight		
Dust and waterproof	Meet IEC529, IP42 standard		
Dimension L * W * H	94mm*64mm*162mm		
Material	ABS+pc	Weight : 207g including cable, without stand	



TWINCOM INC.

www.twincom.com.tw

9F, No. 27-1, Lane 169, Kang Ning St., His Chih Dist., 221, New Taipei City, Taiwan, R.O.C.

TEL : 886-2-26959341(Rep.) FAX : 886-2-26959343 E-Mail : twincom@ms3.hinet.net

